

# Wavelet™ V2

## Industrial IoT Edge Device



### Compatible

Connect any sensor to any software system

### Cost-effective

Save time and money with plug-and-play installation

### Cybersecure

Encryption, authentication and remote updates

### Comprehensive

Encompassing all required equipment and services

## DELIVERING DECISIONS FROM FIELD ASSETS DATA

Ayyeka's Wavelet™ is a ruggedized, battery-powered, wireless Industrial Internet of Things (IIoT) edge device. Seamlessly combined with powerful software, the Wavelet™ offers continuous monitoring and situational awareness. Our end-to-end solution helps municipal and industrial operators increase efficiency, reduce downtime and failures, and improve compliance.

The Wavelet™ is designed for compatibility and interoperability to connect decision-makers with their critical assets. The device generates and securely transmits sensor data to a software platform, where it can be managed and integrated into third-party applications, such as SCADA, data analytics, and GIS.

Through the creation and management of data from field assets, Ayyeka's solution transforms and adds intelligence to new and existing infrastructure networks alike.

## Data & Software

|                              |  |
|------------------------------|--|
| <b>Data hosting</b>          | Cloud or on-premises                       |
| <b>Cyber-security</b>        | TLS 1.2 protocol (AES-256)                 |
| <b>Software integration</b>  | REST API, CSV                              |
| <b>SCADA integration</b>     | CSV, DNP3, OPC-UA                          |
| <b>IoT software platform</b> | Web-based from desktop, tablet, and mobile |
| <b>AyyekaGo mobile app</b>   | iOS, Android                               |
| <b>Data export options</b>   | CSV, FTP                                   |
| <b>Device memory</b>         | 8 GB                                       |
| <b>Data communication</b>    | Two-way authentication                     |
| <b>Alarm threshold</b>       | Up to 4 per data stream                    |
| <b>Alert notification</b>    | SMS, email, voice                          |
| <b>System health check</b>   | Included                                   |

## Power

|                                   |  |
|-----------------------------------|--|
| <b>Primary power supply</b>       | Internal lithium battery (field-replaceable and non-rechargeable), 3.9 V DC 3A |
| <b>Internal battery capacity</b>  | 32Ah   |
| <b>Battery life</b>               | Up to 5+ years   |
| <b>Battery life notifications</b> | Included   |
| <b>External power</b>             | 6-24VDC automatic power source switching                                       |

## Sensors Input

|                               |  |
|-------------------------------|--|
| <b>Sensor ports</b>           | 3 ports; supports up to 12 sensors using cable splitters                         |
| <b>Sensor connection</b>      | Wired with M12 connectors  |
| <b>Serial interfaces</b>      | RS485, RS232, SDI-12   |
| <b>Serial protocols</b>       | Modbus RTU, ASCII, custom  |
| <b>Serial channels</b>        | 16   |
| <b>Analog channels</b>        | 4 (4-20 mA, 0-24 V)  |
| <b>Digital input channels</b> | 5 dry contact, open drain<br>Pulse counting: up to 2 at 39Hz max pulse frequency |
| <b>Digital output channel</b> | 5 at 0V/2.8V<br>Up to 3 simultaneously   |
| <b>Sensor power supply</b>    | 12V or 3.6V, 350mA   |

## Connectivity

|                          |  |
|--------------------------|--|
| <b>Cellular</b>          | 4G/3G/2G   |
| <b>LPWAN</b>             | LoRaWAN  |
| <b>SIM card(s)</b>       | Dual SIM slots, 3FF  |
| <b>Cellular roaming</b>  | Global multi-network SIM(s); data plan included for up to 180+ countries |
| <b>Configuration</b>     | Bluetooth Low Energy (BLE), remotely (over-the-air), USB connection      |
| <b>Data transmission</b> | Periodic, data-dependent   |
| <b>Antenna</b>           | External antenna & backup internal antenna                               |
| <b>Built-in GPS</b>      | Included   |

## Mechanical Enclosure

|                               |  |
|-------------------------------|--|
| <b>Dimensions (W x H x D)</b> | 13.2 cm x 16.5 cm x 7.3 cm (5.2 in. x 6.5 in. x 2.9 in.) |
| <b>Weight</b>                 | 0.9 kg (2.0 lbs)   |
| <b>Enclosure material</b>     | Polycarbonate with ABS (UL 94V-0 and UV-resistant)       |
| <b>Ingress protection</b>     | IP 68 / NEMA 6P  |
| <b>Operating temperature</b>  | -40° to +80°C (-40° to 176°F)                            |
| <b>Storage temperature</b>    | -40° to +80°C (-40° to 176°F)                            |

## Certifications

|                           |  |
|---------------------------|--|
| <b>Safety</b>             | EN 61010-1 2010<br>IEC 61010-1                       |
| <b>FCC</b>                | FCC Part 15 Subpart B                                |
| <b>EMC</b>                | EN 301 489-1 V2.1.1 2017<br>EN 301 489-7 V1.3.1 2005 |
| <b>Spurious emissions</b> | EN 301 511 V12.5.1 2017                              |
| <b>Radiated emissions</b> | EN 301 908-1 V11.1.1 2016                            |
| <b>IP68 / NEMA6P</b>      | EN 60529:1992+A2:2013<br>IEC 60529:1989/AM1:1999     |
| <b>CE</b>                 | Approved   |

<sup>1</sup> Actual battery lifetime depends on sensor power consumption as well as sampling and transmission frequency.

All statements concerning specifications and operating conditions of the Wavelet correspond to the best information available at the time of printing.  
Subject to change without prior notice.

April 2020 V2 P/N 0100709

